

# Feather Lock™




## The Feather Lock™ Slat provides an economical and attractive way to enhance any chain link fence.

Pexco is the largest manufacturer of Feather Lock Slats, which are marketed under the PDS® brand name. With over 30 years of experience extruding these innovative, proprietary products, you are assured of the highest standards in quality—from the raw materials used in manufacturing to the finished product in your fence. This design utilizes a self-locking mechanism located near the top of the slats which also creates extra privacy at eye level where it counts most.

### Design

Feather Lock Slats are flat and tubular in shape, with our unique patented 10" self-locking design feature section at the top of the slat which holds it in place without the need for a locking channel.

### Standard Heights

4, 5, 6, 7, 8, 10 and 12 feet.

### Wind Load and Privacy Factor

Approximately 75%.

### Slat Length

1½" shorter than the overall height of fence.

**Chainlink Privacy Slats**  
**Streetsboro, OH 44240**  
**330.650.9226**

### Colors\*



\* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching.

# Feather Lock™ Product Specifications



Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag	Approx. Coverage Per Box
Feather Lock	1½" 1 <sup>21</sup> / <sub>32</sub> "	2" 2¼"	9,11 or 11½	82 78	10 linear feet 10 linear feet

### Materials

The Feather Lock product is extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

### Durability

Pexco PDS® Fence Products are resistant to: severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates and common environmental pollutants.

### Maintenance

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

### Wind Load Disclaimer

Pexco will not be responsible for fence damage resulting from wind load conditions due to insufficient structural support.

### Limited Warranty

Feather Lock carries a 25-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.

### HDPE Technical Properties

Property	Value
Melt Index	(.6) A low melt index indicates improved stress and crack resistance.
Density	(.957) Polyethylene ranges anywhere from .914 to .960 in density. A higher density yields maximum stiffness without becoming overly brittle.
Minimum Temp.	(-76° F) Polyethylene stays flexible even at this temperature extreme.
Maximum Temp.	(250° F) Polyethylene does not distort until reaching this temperature.
Tensile Strength	(3,700 psi) Material will not suffer distortion at lesser loads or impacts.

**Chainlink Privacy Slats**  
**Streetsboro, OH 44240**  
**330.650.9226**

Contact your local fence professional for more information about our complete line of enhancement products.

